

Titan X Mist Sprayer

Commercial High Performance – 3pt PTO Driven

Low Volume 0-300 PSI

Equipment Specifications:

Frame	Heavy duty 3-point stump jumper design, powder coat paint, pre-punched fork lift compatible frame with category I hitch pins and category II sleeve. Narrow quick hitch compatible.
Tank	100-gallon polyethylene
Pump	6-roller stainless steel Up to 22 gpm
Plumbing	Inline nylon 50 mesh line strainer, pressure regulator, glycerin filled pressure gauge (98% more accurate), hydro-jet continuous flow agitation, electric liquid flow on/off solenoid valve, switch and wiring harness
Fan	19.5" class III industrial huck riveted fan with safety rings (extends fan life 3-5 years), 210° (right to left) rotation with electric actuator and polyethylene 4-nozzle cannon volute
Power	Power Take Off with PTO shaft (540 rpm – 30hp gasoline or 18hp diesel engine minimum required – 200hp maximum)
Dimensions	49"L x 39"W x 61"H, frame width 32", empty weight 571 lbs

100-gallon unit

\$7,495.00

Options:

1-way 11-nozzle Adjustable Vertical Volute \$375.00

2-way 10-nozzle Orchard/Vineyard Volute \$1,199.00



90-160 Feet Maximum
Working Spray Distance
Vertical Spray of 75-95 Feet



Tyson Becker
Mr. Mister Applicators Inc.
Box 1167
Yorkton, SK S3N 2X3
(P) 306.621.3100
(F) 306.782.2790
(E) info@mrmister.ca
www.mrmister.ca

